Model: NAZARI ASILAH
Codes: 100213765 - L138001041
Group: G-231
Format: 11,5X11,5X1-1,1
Thickness: 11 mm



## RECOMMENDATIONS

| | | |
|---|---|---|
| Recommended adhesive | 100043280 TIXOCEM PLUS | |
| Recommended adhesive (wet area) | 100043280 TIXOCEM PLUS | |
| Recommended joint | 100236419 COLORSTUK BEIGE N | |
| Recommended joint (wet area) | 100236419 COLORSTUK BEIGE N | |

## DIMENSIONAL FEATURES

| | | |
|---|---|---|
| Length and width deviation | (±0.5%x±0.5%x±10%) mm | UNE-EN ISO 10545-2* |
| Orthogonality deviation | ±0.5% MM | UNE-EN ISO 10545-2* |
| Side straightness deviation | ±0.3% MM | UNE-EN ISO 10545-2* |
| Surface flatness deviation | (+0.5%/-0.3%) MM | UNE-EN ISO 10545-2* |

## FEATURES

Material with surface with the ability to produce reflections.

Material suitable for use on shower walls.

Material suitable for use on indoor walls.

## PHYSICAL PROPERTIES

| | | |
|---|---|---|
| Breaking strength | >600 N | UNE-EN ISO 10545-4* |
| Coefficient of linear thermal expansion | <7 1/(10E6*°K) | UNE-EN ISO 10545-8* |
| Crack resistance | Meets | UNE-EN ISO 10545-11* |
| Expansion due to moisture | <0.6 mm/m | UNE-EN ISO 10545-10* |
| Flammability | A1 | UNE-EN 13501-1* |
| Resistance to thermal shock | Meets | UNE-EN ISO 10545-9* |
| Water absorption | >10% (BIII) | UNE-EN ISO10545-3* |

## CHEMICAL PROPERTIES

| | | |
|---|---|---|
| Resistance to chemicals | GA/GLA/GHA | UNE-EN ISO 10545-13* |
| Stain resistance | Clase 5 | UNE-EN ISO 10545-14* |

## PACKING

| | | |
|---|---|---|
| Base unit | PIECES | |
| Boxes | 0.3967 M2/BOX | |
| Gross weight | 16.2571 KG/M2 | |
| Net weight | 15.6522 KG/M2 | |
| Pallets | 33.7237 M2/PAL | |
| Sale unit | M2 | |
| Units | 0.0132 M2/PIECE | |