Model: AC5 CEMENT 1L ANTHRACITE
Codes: 100244843 - L165004433
Group: G-222
Format: 60,1X118,4X0,8
Thickness: 8 mm



ADDITIONAL NOTES

High resistance to water and moisture as long as the instructions for installation of this product for these cases are followed.

FEATURES

- Beveled cut on all 4 edges of the board for emphasizing size
- 5 year warranty for commercial use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.
- 5-year warranties on laminate models installed for residential use that are listed as suitable for bathrooms and kitchens.
- Is suitable for installing on water radiant heating
- PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests
- 23. Intensive residential
- High quality decorative film laminate that simulates the aesthetics of cement floors, as well as floors with rust effects. Exclusive laminate for its aesthetics and piece format that simulates large-format ceramics.
- Suitable for bathroom and kitchen floors for residential use, provided that the product's installation instructions are always followed.
- Installation system where gluing the boards to the floor is not necessary. They are installed on a foam and joined together
- 25 year warranty for domestic use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.
- Format where only one board has been used to finish the entire base surface
- Floor capable of dissipating excess electrical charges and distribute them over its entire surface
- Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.
- 33. Intensive commercial
- AC5 Abrasion-resistance level as per Standard UNE-EN 13329

DIMENSIONAL FEATURES

Difference in height among items	medio≤0.10 mm; max≤0.5 mm	UNE EN 13329*
Dimensional variations related to changes in relative moisture	medio≤0.9 mm-max≤0.9 mm	UNE EN 13329*
Flatness of item (f)	Transversal: cóncava≤0.15%-convexa≤0.20%/Longitudinal: cóncava≤0.5%-convexa≤1%	UNE EN 13329*
Item thickness	≤0.50 del valor nominal MM	UNE EN 13329:2016*
Joint between items	Medio≤0.15 mm; max≤0.20 mm	UNE EN 13329*
Length of face	Longitud≤1500 mm Δl≤0.5 mm	UNE EN 13329*
Punching	SIN CAMBIOS VISIBLES	EN ISO 24343-1*
Squareness of the item (q)	max≤0.20 mm	UNE EN 13329*
Straightness of face	max≤0.30 mm	UNE EN 13329*
Surface stripping	≥1.25	UNE EN 13329*
Uv light fastness	Grado 4 en escala de grises	EN 20105-A02*
Width of face	Δ≤0.10 mm del valor nominal/max-min≤0.20 mm	UNE EN 13329*

LABORATORY TESTS

Castor chair effect	SIN DAÑOS VISIBLES	EN 425*
Evaluation of propensity to accumulation of electrostatic charges	≤2 kV	EN 1815*
Fire resistance	Bfl-s1	EN 13501*
Formaldehyde emissions	E1	EN 712-2*
Furniture leg effect	SIN DAÑOS VISIBLES	EN 424*
Impact resistance	CLASE IC3	EN13329 tabla 2*
Moisture upon leaving factory	Entre 4 Y 10%	
Resistance to abrasion	AC5	UNE EN 13329:2000*
Resistance to staining	Grupo 1-2≥5/Grupo 3≥4	EN-438-2 / EN 13329*
Slip resistance (cls)	Húmedo: Clase 1/Seco: Clase 3	UNE-ENV 12633*
Swelling in thickness	≤10%	EN 13329*
Tensile strength of joints	F≥1 kN/ml	UNE EN 13329*

PACKING

Base unit	PIECES
Boxes	2.1348 M2/BOX
Gross weight	8.9547 KG/M2
Net weight	8.6202 KG/M2
Pallets	145.1631 M2/PAL
Sale unit	M2
Square meters	1 M2
Units	0.7116 M2/PIECE

SPECIAL PIECES

SAP	KEA	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100245140	L165004454	IGUALACION CEMENT 1L ANTHRACITE 4X270X1	G-155	20 ST/CS	1000 ST/PAL	9.26 ST/M2	ST	ST	0.7 KG/ST	0.72 KG/ST
100245114	L167013156	MAMPERLAN AC5 CEMENT 1L ANTHRACITE 120X7	G-163	2 ST/CS	200 ST/PAL	11.9 ST/M2	ST	ST	1.58 KG/ST	1.64 KG/ST
100245127	L165004444	TRANSICION CEMENT 1L ANTHRACITE 4X270X1	G-155	20 ST/CS	1000 ST/PAL	9.26 ST/M2	ST	ST	0.7 KG/ST	0.72 KG/ST
100245117	L165004459	ZOCALO CEMENT 1L ANTHRACITE 8X220X1,5	G-107	14 ST/CS	560 ST/PAL	5.68 ST/M2	ST	ST	1.8 KG/ST	1.86 KG/ST