Model:
Codes: 100245937 - L167013199
Group: G-246
Format:
Thickness: 7.5 mm



COMPOSITION



	Size	Material	Type of material
Layer 1	0.2	Wear layer	Capa de uso con protección de Corindón
Layer 2	0.03	Capa decorativa	Capa decorativa con impresión digital
Layer 3	6.2	Mineral	Panel mineral con impresión digital
Layer 4	1	Lignina	Base reductora de sonido

FEATURES

- Installation system where gluing the boards to the floor is not necessary. They are installed on a foam and joined together
- 15 year home use warranty valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use category in accordance with ISO 10582.
- Is suitable for installing on water radiant heating
- Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.
- Water-and-moisture resistant, suitable for wet areas such as bathrooms and kitchens
- 5 year warranty for commercial use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.
- Floor capable of dissipating excess electrical charges and distribute them over its entire surface
- High quality decorative film laminate that simulates the aesthetics of cement floors, as well as floors with rust effects. Exclusive laminate for its aesthetics and piece format that simulates large-format ceramics.

LABORATORY TESTS

Abrasion resistance	AC5 %	EN 13329*
Acoustic insulation	ΔLw=19 DB	EN ISO 717-2*
Castor chair effect	No damage %	
Commercial area class	33	UNE EN 13329*
Dimensional stability	<0.01 %	EN 434*
Dynamic coefficient of friction	Clase DS	EN 13893*
Evaluation of propensity to accumulation of electrostatic charges	≤2 KV	EN 1815*
Fire resistance	Bfl-s1	EN 13501*
Formaldehyde emissions	E1	UNE-EN 717-2:1995*
Heat resistance	0.05 M2*°K/W	EN 12664*
Private area class	23	UNE EN 13329*
Residual footprint	0.00 MM	EN 433*
Resistance of the click	<500 KG/M	ISO 24334*
Resistance to chemicals	MUY BUENA	EN 423*
Resistance to microscratching	MSR-A1/MSR-B1	EN 16094*
Resistance to staining	GRADO 5/5 %	
Slip resistance (r)	R10	EN 51130*
Swelling in thickness	0 %	en 317*
Thermal conductivity	1.5 W/M*°K	EN 12524*
Uv light fastness	7/8	ISO 105*

PACKING

Base unit	PIECES
Boxes	1.692 M2/BOX
Gross weight	14.5863 KG/M2
Net weight	14.0733 KG/M2
Pallets	94.752 M2/PAL
Sale unit	M2
Square meters	1 M2
Units	0.423 M2/PIECE

SPECIAL PIECES

SAP	KEA	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100174756	L167012669	ESP. PERF ADH LINKFLOOR ALUMINIO 3,5X270	G-121	10 ST/CS	1000 ST/PAL	10.58 ST/M2	ST	ST	0.37 KG/ST	0.39 KG/ST
100128267	L167901793	ZOCALO ALUMINIO 8X225	G-121	12 ST/CS	696 ST/PAL	5.56 ST/M2	ST	ST	1.57 KG/ST	1.62 KG/ST